Twinning Program 2021/2 Drilling

(up to release of 30th June 2022)

QP & Historic Results Cautionary Statement

This report quotes historic drill results for previous drill campaigns at Berenguela. Aftermath Silver is currently completing the work needed to verify these results, including twinning a selection of historic drill holes. Until this work has been completed the historic results should be treated with caution. The historic results were taken from NI 43-101 Technical Report on the Berenguela property titled "Berenguela Silver-Copper-Manganese Property Update" was filed on SEDAR on February 25, 2021, authored by independent QP's J.M. Shannon P.Geo, M.A. Batelochi MAusIMM (CP), and G.S. Lane FAusIMM, and has an effective date of February 18, 2021, filed on the Aftermath Silver SEDAR profile.

Michael Parker, FAusIMM,, is a non-independent qualified person, as defined by NI 43-101. Mr. Parker has reviewed the technical content of this report and consents to the information provided in the form and context in which it appears.

In order to verify the 2004/5 RC drilling, a targeted program of hole twinning was implemented in the 2021/2 diamond drill campaign. Where appropriate, PQ diameter diamond drill holes for metallurgical sampling were drilled as twins of 2004/5 RC holes. Additionally, selected RC holes from 2004/5 where recoveries were calculated to be low - or impacted by the reporting of frequent voids/lack of samples - were twinned by PQ diamond holes. In both these cases, the twinned RC hole will be replaced by the diamond drill hole in the borehole database used for resource calculations.

In the NRs of 6th, 13th and 29th June 2022, the following twinned holes were reported:

| 2004/5 RC Hole | 2021/2 Diamond Hole | N.R date |
|----------------|---------------------|--------------|
| BER-191 | AFD-021 | 06 June 2022 |
| BER-083 | AFD-025 | 13 June 2022 |
| BER-004 | AFD-026 | 13 June 2022 |
| BER-009 | AFD-027 | 06 June 2022 |
| BER-008/011 | AFD-028 | 06 June 2022 |
| BER-005/012 | AFD-029 | 06 June 2022 |
| BER-006 | AFD-030 | 06 June 2022 |
| BER-013 | AFD-031 | 06 June 2022 |
| BER-165 | AFD-032 | 06 June 2022 |
| BER-164 | AFD-033 | 06 June 2022 |
| BER-185 | AFD-034 | 06 June 2022 |
| BER-183 | AFD-036 | 13 June 2022 |
| BER-184 | AFD-037 | 13 June 2022 |
| BER-102 | AFD-043 | 30 June 2022 |
| BER-101 | AFD-044 | 30 June 2022 |
| BER-101 | AFD-045 | 30 June 2022 |
| BER-078 | AFD-046 | 13 June 2022 |
| BER-077 | AFD-047 | 30 June 2022 |

The position of the RC holes and their twins is as follows:

| Distance of DD from RC | Azimuth RC (degrees) | Azimuth DD (degrees) | Dip RC (degrees) | Dip DD (degrees) | N.R date | | | | |
|---|---|---|---|---|--|--|--|--|--|
| 1.0m to south | 6 | 3.8 | -44 | -45.4 | 06-Jun-22 | | | | |
| 3.6m to north-west | 184 | 182.7 | -45 | -46.6 | 13-Jun-22 | | | | |
| 1.0m to south | 5 | 1.7 | -45 | -44.6 | 13-Jun-22 | | | | |
| 1.6m west | 5 | 5.9 | -45 | -46.6 | 06-Jun-22 | | | | |
| 1.8m west | 0 | 0 | -90 | -89.5 | 06-Jun-22 | | | | |
| 3.2m west | 0 | 0 | -90 | -89.5 | 06-Jun-22 | | | | |
| 2.2m to south-east | 5 | 6.9 | -45 | -46.3 | 06-Jun-22 | | | | |
| 3.4m to south-east | 5 | 6.9 | -45 | -46.3 | 06-Jun-22 | | | | |
| 2.5m to south-east | 0 | 45.9 | -90 | -88.5 | 06-Jun-22 | | | | |
| 3.8m to north-west | 185 | 184.4 | -45 | -46.4 | 06-Jun-22 | | | | |
| 2.3m west | 0 | 0 | -90 | -87.7 | 06-Jun-22 | | | | |
| 2.4m west | 187 | 185.0 | -45 | -45.9 | 06-Jun-22 | | | | |
| 2.0m to west | 187 | 186.8 | -45 | -45.2 | 06-Jun-22 | | | | |
| 2.2m to east | 188 | 185.7 | -45 | -45.0 | 13-Jun-22 | | | | |
| 1.0m to south | 0 | 27.8 | -90 | -87.8 | 13-Jun-22 | | | | |
| 3.4m to west | 9 | 6.8 | -45 | -44.9 | 30-Jun-22 | | | | |
| 6.4m to south-west | 0 | 316.1 | -90 | -83 | 30-Jun-22 | | | | |
| 3.4m to north | 187 | 186.1 | -45 | -45.9 | 30-Jun-22 | | | | |
| 8.0m to south-east | 0 | 171.2 | -90 | -88.0 | 13-Jun-22 | | | | |
| 2.6m to south-west | 185 | 184.8 | -45 | -44.3 | 30-Jun-22 | | | | |
| RC azimuths and dips are as per set out or derived from reports/maps. DD azimuths and dips are averages of downhole surveys. | | | | | | | | | |
| | RC 1.0m to south 3.6m to north-west 1.0m to south 1.6m west 1.8m west 3.2m west 2.2m to south-east 3.4m to south-east 2.5m to south-east 3.8m to north-west 2.3m west 2.4m west 2.0m to west 2.2m to east 1.0m to south 3.4m to west 6.4m to south-west 3.4m to north 8.0m to south-east 2.6m to south-west 4 as per set out or derived averages of downhole | Distance of DD from RC (degrees) RC (degrees) 1.0m to south 6 3.6m to north-west 184 1.0m to south 5 1.6m west 5 1.8m west 0 3.2m west 0 2.2m to south-east 5 3.4m to south-east 0 3.8m to north-west 185 2.3m west 0 2.4m west 187 2.0m to west 187 2.2m to east 188 1.0m to south 0 3.4m to west 9 6.4m to south-west 0 3.4m to north 187 8.0m to south-east 0 2.6m to south-west 185 | Distance of DD from RC RC (degrees) (degrees) 1.0m to south 6 3.8 3.6m to north-west 184 182.7 1.0m to south 5 1.7 1.6m west 5 5.9 1.8m west 0 0 3.2m west 0 0 2.2m to south-east 5 6.9 3.4m to south-east 0 45.9 3.8m to north-west 185 184.4 2.3m west 0 0 2.4m west 187 185.0 2.0m to west 187 186.8 2.2m to east 188 185.7 1.0m to south 0 27.8 3.4m to west 9 6.8 6.4m to south-west 0 316.1 3.0m to south-east 0 171.2 2.6m to south-west 185 184.8 | Distance of DD from RC RC (degrees) DD (degrees) DD (degrees) 1.0m to south 6 3.8 -44 3.6m to north-west 184 182.7 -45 1.0m to south 5 1.7 -45 1.6m west 5 5.9 -45 1.8m west 0 0 -90 3.2m west 0 0 -90 3.2m to south-east 5 6.9 -45 3.4m to south-east 5 6.9 -45 2.5m to south-east 0 45.9 -90 3.8m to north-west 185 184.4 -45 2.3m west 0 0 -90 2.4m west 185 184.4 -45 2.0m to west 187 186.8 -45 2.2m to east 188 185.7 -45 1.0m to south 0 27.8 -90 3.4m to west 9 6.8 -45 6.4m to south-west 0 316.1 -9 | Distance of DD from RC RC DD (degrees) Dip RC (degrees) Dip DD (degrees) 1.0m to south 6 3.8 -44 -45.4 3.6m to north-west 184 182.7 -45 -46.6 1.0m to south 5 1.7 -45 -46.6 1.6m west 5 5.9 -45 -46.6 1.8m west 0 0 -90 -89.5 3.2m west 0 0 -90 -89.5 2.2m to south-east 5 6.9 -45 -46.3 3.4m to south-east 5 6.9 -45 -46.3 2.5m to south-east 0 45.9 -90 -88.5 3.8m to north-west 185 184.4 -45 -46.4 2.3m west 0 0 -90 -87.7 2.4m west 187 185.0 -45 -45.9 2.0m to west 187 186.8 -45 -45.0 1.0m to south 0 27.8 -90 | | | | |

Prior to the twinning program, a study of the reported weights of the 2004/5 RC samples delivered to the assay laboratory was undertaken. In conjunction with studies of the drilling and sampling methodology employed in 2004/5, these weights were taken as a proxy of sample recovery on a metre for metre basis, and a calculated recovery was derived per mineralised intersection. A comparison was made between angle and vertical RC holes with no significant variance noted. No specific density variations were applied given the globally selective nature of the analysis in mineralised intersections, and instead a broad range of calculated recoveries was adopted. The results are summarised as follows:

Overall average dry and split delivered sample weight from mineralised intersections of 1m drill length (RC) was calculated as $3.63~\rm kg$

Reported sample weight >= 3.63 kg Calculated Recovery 100%

Reported sample weight 2.72 to 3.62kg Calculated Recovery 75 to 100%

Reported sample weight 1.82 to 2.72kg Calculated Recovery 50 to 75%

Reported sample weight 0.91 to 1.82kg Calculated Recovery 25 to 50%

Reported sample weight <= 0.90kg Calculated Recovery < 25%

Preliminary observations from the hole-twinning program are the following:

- a) The 2021/2 diamond drilling successfully overcame the technical problems of recovery initiated by encountering mining voids or soft/wet samples in the 2004/5 RC program. Core recoveries, discounting the identified mining voids, were almost all in the high 90 percent range. In the case of BER-005 and BER-012 (a redrill), 6 zones of voids/poor recovery totalling 11m hole-length and one void of 5m hole-length were not encountered in the twin diamond-hole AFD-029. AFD-029 traversed the same mineralised zone over 97.60m hole length with 2 minor voids totalling 1.6m and core recovery of 98%. Poor calculated recoveries in BER-005 were obviated, and failure to reach target depth in BER-012 was addressed by AFD-029 that successfully reached planned depth after traversing the target zone. In some cases, the twin program confirmed the voids encountered in the RC program. For example, BER-165 was twinned by AFD-032 and both holes reported two voids with similar hole-depth positions and widths. In other cases such as AFD-044, voids encountered in the diamond drilling, were not reported in the RC twin hole BER-103 which reflects the much more discrete nature of diamond drilling methodology versus RC.
- b) In terms of comparative grades (see tables below), preliminary observations on this sub-set of twinned holes show that the diamond holes generally reported grades on parity or higher than the RC holes. Intervals of mineralisation were generally more discrete in the diamond drill program, but generally compared well to the RC. Those RC holes with high calculated recoveries had intersections similar to the diamond drilling (ie, BER-191 and AFD-021, BER-013 and AFD-031, BER-102 and AFD-043. It should be noted that BER-013 ended in mineralisation and AFD-031 successfully continued to intersect an additional hole length of 17.65m @ 1.81% Cu). In the case of BER-164, an RC hole with moderate calculated recovery, and AFD-033, two distinct zones of mineralisation can be compared in both of which the diamond hole reported higher grades for Ag, Cu, and Mn. In the case of BER-185 twinned with AFD-034, the RC hole reported poor calculated recoveries in the mineralised zone (25-50%) and the corresponding diamond hole reported higher Ag grades (in this particular case, more than double). A similar effect is noted between BER-078 and AFD-046 where an ultra high-grade Ag intersection is doubled in grade with a slight reduction in intersection width. In this case, Mn and Zn are appreciably lower in the diamond hole demonstrating potential washing of fines and upgrading of heavy mineral content in the RC program. It is important to note that not all DD intersections are better. A case of grade reduction, the only significant one so far in 16 twinned holes, occurs between the RC hole BER-083 and DD hole AFD-025 where the Cu grade is reduced by 50% from 1.66% to 0.83% in a 20.3m wide intersection from surface. Examination of the individual sample weights in the RC shows that some higher-grade Cu was reported in poor recovery samples indicating a recovery/grade bias in this particular case.
- c) In terms of contamination and grade-smearing caused by the RC method, particularly in wet holes, some potential examples have been addressed by these twin holes. In particular, in BER-009, twinned by diamond hole AFD-027, RC hole conditions

deteriorated at 37m and subsequently a low calculated recovery interval (25-50%) from 40 to 46m reported high Ag grades not repeated in the diamond drilling (probably caused by washing of the RC sample in the hole). Subsequent sample loss at 46m in BER-009 was followed by a low calculated recovery 5m interval (25-50%) with moderate Ag and Cu grades from 48m hole depth that is likely to be contamination. Several voids reported in the diamond hole AFD-027 were not reported in the RC hole. This example of loss of hole condition in the RC program and sampling/grade errors has been successfully addressed by AFD-027. AFD-027 terminated with an intersection of 24.75m from hole depth 53.95m with higher grades than the comparable intersection in BER-009. As mentioned above, examination of individual metre sample recoveries in BER-083 point to a case of upgrading Ag and Cu grades over short intervals — an effect minimised by the twin DD hole.

Aftermath specifically sought out examples in the RC database of poor calculated recoveries related to higher grade intervals, and/or loss of hole conditions leading to poor calculated RC recoveries. Aftermath systematically twinned the relevant RC holes with the diamond drilling program (examples being the twinning of BER-004, BER-005/12, BER-164, BER-165, BER-183, BER-185, BER-009, BER-008/11, and BER-077 in results released to date). The diamond holes will replace the RC holes in the resource database.

TABULATED SUMMARY OF RESULTS (in order of DD hole AFD number)

BER-191 Twinned by AFD021

| | | From | То | Interval | | | | | Calculated |
|------|---------|------|-----|----------|--------|------|------|------|------------|
| Year | Hole | (m) | (m) | (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2005 | BER-191 | 1 | 16 | 15 | 58 | 4.10 | 0.81 | 0.29 | 100% |
| 2005 | and | 20 | 26 | 6 | 52 | 4.46 | 0.53 | 0.47 | 100% |
| 2005 | and | 28 | 33 | 5 | 66 | 3.77 | 0.39 | 0.43 | 100% |
| 2005 | and | 38 | 113 | 75 | 86 | 6.46 | 0.97 | 0.57 | 100% |

| | | From | То | Interval | | | | | Measured | |
|---|--------|-------|--------|----------|--------|------|------|------|----------|--|
| Year | Hole | (m) | (m) | (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery | |
| 2021/2 | AFD021 | 11.00 | 19.40 | 8.40 | 43 | 5.52 | 0.54 | 0.34 | 100% | |
| 2021/2 | and | 22.40 | 74.20 | 48.00 | 65 | 5.41 | 0.72 | 0.52 | 99%* | |
| 2021/2 | and | 77.20 | 89.95 | 12.75 | 82 | 8.00 | 1.56 | 0.70 | 99% | |
| 2021/2 | and | 92.50 | 109.50 | 17.00 | 97 | 6.79 | 1.15 | 0.48 | 96% | |
| *void 59.2 to 62.2m not entered in recovery calculation | | | | | | | | | | |

BER-083 Twinned by AFD025

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Calculated Recovery | | |
|----------|---|-------------|-----------|--------------|--------|------|------|------|------------------------|--|--|
| 2005 | BER-083 | 0 | 19 | 19 | 132 | 8.38 | 1.66 | 0.39 | 75-100% | | |
| | | | | | | | | | | | |
| | | From | То | | | | | | Measured | | |
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery | | |
| 2021/2 | AFD025 | 0.00 | 20.30 | 18.90 | 96 | 8.07 | 0.83 | 0.34 | 90%* | | |
| 2021/2 | AFD025 | 29.30 | 33.50 | 4.20 | 75 | 3.83 | 0.28 | 0.22 | 100% | | |
| *voids a | *voids at 8.5 to 8.9m, and 10.6 to 11.6m not entered in recovery calculations | | | | | | | | | | |

BER-004 Twinned by AFD026

| | | | То | | | | | | Calculated |
|------|---------|----------|-----|--------------|--------|-------|------|------|------------|
| Year | Hole | From (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2004 | BER-004 | 0 | 9 | 9 | 54 | 12.23 | 1.12 | 0.38 | 100% |
| 2004 | | 9 | 12 | VOID | | | | | |
| 2004 | and | 12 | 23 | 11 | 117 | 18.29 | 1.18 | 0.56 | 50-75% |
| 2004 | and | 37 | 51 | 14 | 71 | 4.74 | 0.85 | 0.40 | 50-75% |
| 2004 | and | 58 | 65 | 7 | 50 | 12.79 | 0.66 | 0.45 | 100% |
| 2004 | and | 71 | 83 | 12 | 38 | 15.66 | 1.22 | 0.32 | 50-75% |

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Measured Recovery |
|--------|---------|----------|-----------|--------------|--------|-------|------|------|----------------------|
| 2021/2 | AFD-026 | 1.00 | 29.90 | 26.85 | 95 | 12.40 | 1.13 | 0.38 | 99%* |
| 2021/2 | AFD-026 | 32.90 | 79.10 | 46.20 | 79 | 9.93 | 1.19 | 0.45 | 98% |

^{*}voids at 8.1 to 9.8m, and 28.65 to 28.9m not entered in recovery calculations

BER-009 Twinned by AFD027

| | | From | То | | | | | | Calculated |
|------|---------|------|-----|--------------|--------|-------|------|------|------------|
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2004 | BER-009 | 5 | 20 | 15 | 73 | 11.57 | 1.34 | 0.25 | 75-100% |
| 2004 | and | 28 | 34 | 6 | 48 | 4.71 | 1.29 | 0.31 | 50-75% |
| 2004 | | 37 | 40 | VOID | | | | | |
| 2004 | and | 40 | 46 | 6 | 343 | 20.07 | 0.66 | 1.27 | 25-50% |
| 2004 | | 46 | 48 | VOID | | | | | |
| 2004 | and | 48 | 53 | 5 | 90 | 18.29 | 0.67 | 1.05 | 25-50% |
| 2004 | and | 58 | 82 | 24 | 98 | 12.13 | 1.01 | 0.64 | 75-100% |

| | | From | То | | | | | | Measured |
|--------|------|-------|-------|--------------|--------|-------|------|------|----------|
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| | AFD- | | | | | | | | |
| 2021/2 | 027 | 5.50 | 19.30 | 13.80 | 62 | 11.36 | 1.09 | 0.25 | 99% |
| 2021/2 | and | 27.75 | 30.75 | 3.00 | 49 | 3.60 | 2.31 | 0.26 | 97% |
| 2021/2 | and | 35.75 | 42.75 | 7.00 | 40 | 2.13 | 0.81 | 0.20 | 96% |
| 2021/2 | and | 53.95 | 84.00 | 24.75 | 228 | 13.27 | 1.29 | 0.61 | 96%* |

 $[\]star$ voids at 57.6 to 60.6m, 76.9 to 77.9m, and 79.7 to 81.0m not entered in recovery calculation

BER-008 and Redrill BER-011 Twinned by AFD028

| | | From | То | | | | | | Calculated |
|------|-----------------|------|-----|--------------|--------|-------|------|------|------------|
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2004 | BER-008 | 16 | 23 | 7 | 165 | 15.91 | 1.13 | 0.42 | 25-50% |
| 2004 | | 28 | 37 | VOID | | | | | |
| 2004 | and | 37 | 53 | 16 | 94 | 12.17 | 1.78 | 0.40 | 25-50% |
| 2004 | | 53 | 75 | VOID | | | | | |
| 2004 | and | 75 | 80 | 5 | 67 | 17.42 | 1.49 | 0.43 | <25% |
| | | | | | | | | • | |
| 2004 | BER-011 | 0 | 10 | 10 | 49 | 7.37 | 0.88 | 0.23 | 50-75% |
| 2004 | | 11 | 12 | VOID | | | | | |
| 2004 | and | 12 | 56 | 44 | 106 | 14.52 | 1.54 | 0.39 | 100% |
| 2004 | | 56 | 58 | VOID | | | | | |
| 2004 | and (ends in | 58 | 76 | 18 | 89 | 14.70 | 2.55 | 0.31 | |
| | min) | | | | | | | | 100% |
| | | From | То | | | | | | Measured |

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Measured Recovery | | |
|-----------|---|-------------|-----------|--------------|--------|-------|------|------|----------------------|--|--|
| | AFD- | | | | | | | | | | |
| 2021/2 | 028 | 8.60 | 31.60 | 21.70 | 151 | 16.12 | 1.37 | 0.35 | 99%* | | |
| | AFD- | | | | | | | | | | |
| 2021/2 | 028 | 37.20 | 74.80 | 36.15 | 168 | 15.49 | 1.82 | 0.49 | 99%* | | |
| *voids at | *voids at 26.2 to 27.5m, and 56.0 to 57.45m not entered in recovery calculation | | | | | | | | | | |

BER-005 and Redrill BER-012 Twinned by AFD029

| | | | To | | Ag | Mn | | | Calculated |
|-----------|-----------|----------------|-----------|-------------------|--------|-------|------|------|------------|
| Year | Hole | From (m) | (m) | Interval (m) | g/t | % | Cu % | Zn % | Recovery |
| 2004 | BER-005 | 5 | 7 | VOID | | | | | |
| 2004 | BER-005 | 7 | 12 | 5 | 44 | 6.04 | 1.45 | 0.24 | 50-75% |
| 2004 | | 12 | 13 | VOID | | | | | |
| 2004 | and | 13 | 19 | 6 | 79 | 13.68 | 0.96 | 0.46 | 50-75% |
| 2004 | | 19 | 21 | VOID | | | | | |
| 2004 | and | 21 | 31 | 10 | 40 | 6.41 | 0.65 | 0.23 | 50-75% |
| 2004 | | 31 | 33 | VOID | | | | | |
| 2004 | and | 33 | 38 | 5 | 331 | 15.76 | 1.01 | 0.42 | 50-75% |
| 2004 | | 38 | 40 | VOID | | | | | |
| 2004 | and | 40 | 63 | 23 | 330 | 14.64 | 1.65 | 0.55 | 100% |
| 2004 | | 77 | 79 | VOID | | | | | |
| 2004 | and | 79 | 98 | 19 | 66 | 17.36 | 2.01 | 0.40 | 25-50% |
| | | | | | | | | | |
| 2004 | BER-012 | 6 | 20 | 14 | 55 | 13.79 | 0.85 | 0.36 | 100% |
| 2004 | and | 23 | 66 | 43 | 191 | 12.59 | 1.98 | 0.35 | 100% |
| 2004 | | 66 | 71 | VOID | | | | | |
| 2004 | and (ends | 71 | 77 | 6 | 327 | 15.64 | 2.91 | 0.48 | |
| | in min) | | | | | | | | 75-100% |
| | | | | | | | | | |
| | | | То | | Ag | Mn | | | Measured |
| Year | Hole | From (m) | (m) | Interval (m) | g/t | % | Cu % | Zn % | Recovery |
| 2021/2 | AFD-029 | 0.00 | 99.20 | 97.60 | 188 | 15.17 | 1.70 | 0.43 | 98%* |
| 2021/2 | inc | 31.20 | 35.20 | 4.00 | 821 | 19.03 | 1.42 | 0.54 | 100% |
| 2021/2 | inc | 73.10 | 93.10 | 20.00 | 268 | 21.73 | 2.95 | 0.47 | 99% |
| * voids a | | 2m and 40.8 to | o 42.1m r | ot entered in red | covery | | | | |

BER-006 Twinned by AFD030

| | | | То | | Ag | Mn | | | Calculated |
|--------------------|----------------|------------------|-----------|-----------------------|-----------|---------|-------------|------------------|----------------------|
| Year | Hole | From (m) | (m) | Interval (m) | g/t | % | Cu % | Zn % | Recovery |
| 2004 | BER-006 | 1 | 6 | 5 | 25 | 5.56 | 0.51 | 0.16 | 100% |
| 2004 | and | 8 | 38 | 30 | 70 | 8.62 | 1.07 | 0.29 | 50-75% |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | То | | Ag | Mn | | | Measured |
| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Measured Recovery |
| Year 2021/2 | Hole AFD030 | From (m) 1.30 | _ | Interval (m) 35.60 | | | Cu % | Zn % 0.23 | |

BER-013 Twinned by AFD031

| | | From | То | | | | | | Calculated |
|------|-----------------|------|-----|--------------|--------|------|------|------|------------|
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2004 | BER-013 | 8 | 20 | 12 | 48 | 4.60 | 0.91 | 0.20 | 100% |
| 2004 | and (ends in | 49 | 67 | 18 | 45 | 8.23 | 1.00 | 0.22 | 1000/ |
| | min) | | | | | | | | 100% |

| | | From | То | | | | | | Measured |
|--------|--------|-------|-------|--------------|--------|------|------|------|----------|
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2021/2 | AFD031 | 8.2 | 21.1 | 11.8 | 30 | 3.46 | 0.77 | 0.15 | 98%* |
| 2021/2 | and | 23.1 | 29.45 | 6.35 | 46 | 2.42 | 0.57 | 0.14 | 100% |
| 2021/2 | and | 50.15 | 70.2 | 17.95 | 67 | 5.34 | 1.11 | 0.26 | 97%* |
| 2021/2 | and | 82.2 | 99.85 | 17.65 | 36 | 6.48 | 1.81 | 0.25 | 87% |

^{*}Voids at 10.2 to 10.7m, 12.6 to 13.2m, 54.6 to 55.3m, and 65.35 to 65.75m not entered in recovery calculation

BER-165 Twinned by AFD032

| | | From | То | | | | | | Calculated |
|------|---------|------|-----|--------------|--------|-------|------|------|------------|
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2005 | BER-165 | 0 | 9 | 9 | 138 | 16.62 | 2.63 | 0.53 | 50-75% |
| 2005 | | 40 | 41 | VOID | | | | | |
| 2005 | and | 41 | 64 | 23 | 49 | 13.59 | 1.21 | 0.40 | 25-50% |
| 2005 | | 64 | 67 | VOID | | | | | |
| 2005 | and | 67 | 93 | 26 | 79 | 11.82 | 0.87 | 0.42 | 75-100% |

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Measured Recovery |
|--------|--------|-------------|-----------|--------------|--------|-------|------|------|----------------------|
| 2021/2 | AFD032 | 0 | 8.2 | 8.2 | 110 | 27.76 | 1.46 | 0.73 | 95% |
| 2021/2 | and | 37.35 | 92.05 | 51.7 | 48 | 9.81 | 1.02 | 0.30 | 99% |

^{*}voids at 38.45 to 39.45m and 70.4 to 72.4m not entered in recovery calculation

BER-164 Twinned by AFD033

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Calculated Recovery |
|------|---------|-------------|-----------|-----------------|--------|-------|------|------|------------------------|
| 2005 | BER-164 | 12 | 52 | 40 | 68 | 9.25 | 1.06 | 0.22 | 50-75% |
| 2005 | and | 66 | 75 | 9 | 102 | 11.94 | 0.74 | 0.34 | 50-75% |

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Measured Recovery |
|--------|---------|-------------|-----------|-----------------|--------|-------|------|------|----------------------|
| 2021/2 | AFD-033 | 0.00 | 3.40 | 3.40 | 77 | 4.04 | 1.29 | 0.20 | 97% |
| 2021/2 | and | 6.40 | 9.40 | 3.00 | 97 | 1.89 | 0.33 | 0.14 | 97% |
| 2021/2 | and | 14.00 | 56.10 | 39.50 | 104 | 11.41 | 1.38 | 0.24 | 97%* |
| 2021/2 | and | 66.10 | 76.60 | 9.30 | 91 | 14.21 | 1.06 | 0.33 | 95%* |

^{*}voids at 15.7 to 16.5m, 32.1 to 33.1m, 52.5 to 53.3m, and 69.3 to 70.5m not entered in recovery calculation

BER-185 Twinned by AFD034

| | | From | То | Interval | | | | | Calculated |
|------|---------|------|-----|----------|--------|------|------|------|------------|
| Year | Hole | (m) | (m) | (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2005 | BER-185 | 11 | 17 | 6 | 164 | 3.31 | 1.08 | 0.43 | 50-75% |
| 2005 | and | 24 | 58 | 34 | 176 | 6.90 | 0.89 | 0.59 | 25-50% |
| 2005 | | 58 | 61 | VOID | | | | | |
| 2005 | and | 61 | 70 | 9 | 54 | 2.99 | 0.82 | 0.30 | 100% |

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Measured Recovery |
|--------|---------|-------------|-----------|-----------------|--------|-------|------|------|----------------------|
| 2021/2 | AFD-034 | 0.00 | 69.55 | 65.25 | 408 | 5.90 | 0.91 | 0.54 | 98%* |
| 2021/2 | inc | 39.70 | 59.65 | 18.95 | 1162 | 10.60 | 1.12 | 0.86 | 98%* |

^{*}voids at 26.4 to 27.2m, 45.2 to 46.2m, and 59.65 to 62.15m not entered in recovery

BER-183 Twinned by AFD036

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Calculated Recovery |
|--------|---------|-------------|-----------|--------------|--------|-------|------|------|------------------------|
| 2005 | BER-183 | 32 | 63 | 31 | 64 | 13.01 | 1.63 | 0.52 | 50-75% |
| | | | | | | | | | |
| | | From | То | | | | | | Measured |
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| | 1 | | | | | | | | |
| 2021/2 | AFD036 | 29.40 | 46.35 | 16.95 | 50 | 18.40 | 1.61 | 0.76 | 99% |

BER-184 Twinned by AFD037

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Calculated Recovery |
|--------|---------|-------------|-----------|--------------|--------|-------|------|------|------------------------|
| 2005 | BER-184 | 12 | 20 | 8 | 255 | 26.65 | 0.78 | 0.80 | 50-75% |
| 2005 | | 28 | 30 | VOID | | | | | |
| 2005 | and | 30 | 35 | 5 | 60 | 2.15 | 0.58 | 0.15 | 50-75% |
| | | | | | | | | | |
| | | From | То | | | | | | Measured |
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2021/2 | AFD037 | 11.60 | 19.20 | 7.60 | 243 | 19.67 | 1.28 | 1.06 | 96% |
| 2021/2 | AFD037 | 24.40 | 30.55 | 6.15 | 104 | 2.85 | 0.52 | 0.23 | 100% |

BER-102 Twinned by AFD043

| | | From | | | | | | | Calculated |
|--------|---------|-------|--------|--------------|--------|-------|------|------|------------|
| Year | Hole | (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2005 | BER-102 | 0 | 21 | 21 | 162 | 16.89 | 1.83 | 0.64 | 100% |
| 2005 | and | 24 | 42 | 18 | 66 | 3.35 | 0.97 | 0.22 | 100% |
| 2005 | and | 56 | 64 | 8 | 236 | 18.61 | 0.95 | 0.54 | 100% |
| 2005 | and | 74 | 99 | 25 | 305 | 24.10 | 1.34 | 0.70 | 75-100% |
| | | | | | | | | | |
| | | From | | | | | | | Measured |
| Year | Hole | (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2021/2 | AFD043 | 0.00 | 16.15 | 15.25 | 285 | 23.23 | 1.41 | 0.97 | 92% |
| 2021/2 | AFD043 | 24.60 | 53.35 | 27.75 | 89 | 4.24 | 1.02 | 0.25 | 96% |
| 2021/2 | AFD043 | 57.15 | 66.20 | 9.05 | 338 | 20.31 | 1.35 | 0.71 | 98% |
| 2021/2 | AFD043 | 74.80 | 100.10 | 25.30 | 452 | 23.07 | 1.63 | 0.66 | 97% |

704

655

21.11

29.32

2.67

1.59

0.78

0.69

100%

96%

5.00

9.25

96.05 *voids at 2.3 to 3.2m, and 32.0 to 33.0m not entered in recovery calculation

82.80

BFR-103 Twinned by AFD044

77.80

86.80

2021/2

2021/2

inc

| Hole ER-103 | (m) | (m) | Intorval (m) | | | | | _ |
|----------------|------|----------|-------------------------------|--|---|--|--|---|
| ED 102 | | (/ | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| EK-102 | 0 | 21 | 21 | 137 | 10.71 | 0.78 | 0.50 | 50-75% |
| | | | | | | | | |
| | From | To | | | | | | Measured |
| Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| FD044 | 0.00 | 19.05 | 15.65 | 179 | 11.05 | 1.00 | 0.42 | 95% |
| F | D044 | Hole (m) | Hole (m) (m) D044 0.00 19.05 | Hole (m) (m) Interval (m) FD044 0.00 19.05 15.65 | Hole (m) (m) Interval (m) Ag g/t FD044 0.00 19.05 15.65 179 | Hole (m) (m) Interval (m) Ag g/t Mn % FD044 0.00 19.05 15.65 179 11.05 | Hole (m) (m) Interval (m) Ag g/t Mn % Cu % | Hole (m) (m) Interval (m) Ag g/t Mn % Cu % Zn % |

BER-101 Twinned by AFD045

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Calculated Recovery |
|--------------------|----------------|-------------|-----------|-----------------------|---------------|-------------------|-------------|-------------|------------------------|
| 2005 | BER-101 | 0 | 9 | 9 | 78 | 5.90 | 1.13 | 0.31 | 50-75% |
| 2005 | and | 15 | 26 | 11 | 131 | 5.04 | 0.48 | 0.27 | 50-75% |
| | | | | | | | | | |
| | | | | | | | | | |
| | | From | То | | | | | | Measured |
| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Measured Recovery |
| Year 2021/2 | Hole AFD045 | | | Interval (m) 10.25 | Ag g/t | Mn % 13.09 | Cu % | Zn % | |
| | | (m) | (m) | · · · | | | I | | Recovery |

BER-078 Twinned by AFD046

| Year | Hole | From (m) | To (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Calculated Recovery |
|--------|---------|-------------|-----------|--------------|--------|-------|------|------|------------------------|
| 2005 | BER-078 | 0 | 16 | 16 | 412 | 18.00 | 1.19 | 0.86 | 75-100% |
| 2005 | | 16 | 18 | VOID | | | | | |
| 2005 | and | 18 | 25 | 7 | 726 | 25.10 | 1.13 | 0.91 | 50-75% |
| | | | | | | | | | |
| | | From | То | | | | | | Measured |
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2021/2 | AFD046 | 0.00 | 13.40 | 13.40 | 276 | 16.46 | 1.25 | 0.57 | 100% |
| 2021/2 | AFD046 | 17.75 | 22.85 | 5.10 | 1545 | 13.22 | 1.78 | 0.30 | 100% |

BER-077 Twinned by AFD047

| | | From | То | | | | | | Calculated |
|--|--------|-------|-------|--------------|--------|------|------|------|------------|
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2005 | BER- | 0 | 19 | 19 | 178 | 6.60 | 0.73 | 0.37 | 75-100% |
| | 077 | | | | | | | | |
| 2005 | and | 21 | 38 | 17 | 64 | 6.49 | 1.68 | 0.20 | 75-100% |
| 2005 | and | 41 | 51 | 10 | 61 | 2.26 | 0.66 | 0.14 | 75-100% |
| | | | | | | | | | |
| | | From | То | | | | | | Measured |
| Year | Hole | (m) | (m) | Interval (m) | Ag g/t | Mn % | Cu % | Zn % | Recovery |
| 2021/2 | AFD047 | 0.00 | 51.95 | 51.15 | 116 | 7.41 | 1.54 | 0.27 | 99%* |
| 2021/2 | AFD047 | 88.00 | 96.50 | 8.50 | 210 | 1.26 | 1.05 | 0.10 | 98% |
| *void at 12.8 to 13.6m not entered in recovery calculation | | | | | | | | | |